

TORQUE

GEAR OIL



75W-80 GL5

DATA SHEET

PHYSICAL TECHNICAL DATA	
SAE GRADE	75W80
DENSITY A 20 °C,g/ml (ASTM D4052)	0,890
VISCOSITY 40 °C. cST.(ASTM D445)	70-80
VISCOSITY 100 °C. cST.(ASTM D445)	10-10,5
VISCOSITY INDEX, (ASTM D2270)	120
FLASH POINT °C. (ASTM D92)	220
FREEZING POINT °C. (ASTM D97)	-25

RECOMMENDATION
MB 235.1
FORD SQM - 2C 1011 A
MAN 341
UK MINISTRY OF DEFENSE CS 3000 B

DESCRIPTION

TORQUE GEAR OIL - VALVULINA 75W-80 (GL5) IS A MULTIGRADE OIL FOR EXTREME PRESSURE OF THE LATEST GENERATION, DESIGNED FOR GEARBOXES AND DIFFERENTIALS WITH HYPOID AND HELICAL GEARS IN ALL TYPES OF VEHICLES AND/OR MACHINERY. IT IS MANUFACTURED WITH HIGHLY REFINED BASES AND HIGH TECHNOLOGY ADDITIVES THAT GUARANTEE THE TOUGHEST APPLICATION REQUIREMENTS, EVEN WITH LARGE VARIATIONS IN WORKING TEMPERATURE.

MAIN ADVANTAGES

- EXCELLENT LUBRICATING AND ANTI-WEAR PROPERTIES.
- HIGH RESISTANCE TO OXIDATION AND AGEING.
- GOOD CORROSION PROTECTION.
- LOW OIL CONSUMPTION.
- DOES NOT ATTACK COPPER AND ITS ALLOYS.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUIRES THESE QUALITY LEVELS.

QUALITY LEVELS	
API	GL-5
MIL	L2105 D