

TORQUE

GEAR OIL



75W-80 GL5+LS

DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	75W80
DENSITY AT 20 °C, g/ml (ASTM D4052)	0,875
VISCOSITY 40 °C. cST. (ASTM D445)	75-85
VISCOSITY 100 °C. cST. (ASTM D445)	9,8-10,5
VISCOSITY INDEX, (ASTM D2270)	>140
FLASH POINT °C. (ASTM D92)	195
FREEZING POINT °C. (ASTM D97)	-37

BUILDERS	
MB 235.6	AGMA 250,04
SAE J 2360	ZF TE ML 17A, 17B.
FROM 51517 PART 3 CLP	DAF SCANIA STO 1:0

DESCRIPTION

TORQUE GEAR OIL - VALVE 75W80 (GL5) IS A LATEST GENERATION EXTREME PRESSURE MULTIGRADE SYNTHETIC OIL, FORMULATED FOR GEARBOXES AND DIFFERENTIALS WITH HYPOID AND HELICAL GEARS IN ALL TYPES OF VEHICLES AND/OR MACHINERY, INCLUDING THOSE REQUIRED BY THE STANDARD SLIP LIMITED (LS). IT IS MANUFACTURED WITH HIGHLY REFINED BASES AND HIGH-TECH ADDITIVES THAT GUARANTEE THE TOUGHEST APPLICATION DEMANDS, EVEN WITH LARGE VARIATIONS IN WORKING TEMPERATURE.

- **MAIN ADVANTAGES**
- **EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.**
- **GREAT RESISTANCE TO OXIDATION AND AGING.**
- **GOOD PROTECTION AGAINST CORROSION.**
- **DECREASES OIL CONSUMPTION.**
- **REDUCES THE NOISE INDEX OF THE UNIT OR GEARBOX.**
- **DOES NOT ATTACK COPPER OR ITS ALLOYS.**
- **USABLE IN WINTER AND SUMMER.**
- **LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.**

QUALITY LEVELS	
API	GL5 + LIMITED SLIP (LS) / MT-1
MIL	L2105 D