

# TORQUE

## STEERING FLUID



# PSF

## DATA SHEET

PHYSICAL TECHNICAL DATA	
COLOR	VERDE
VISCOSITY 100 °C.	6,7 cST
VISCOSITY 40 °C.	19,0 cST
VISCOSITY -40 °C.	14200
VISCOSITY INDEX	>300
FLASH POINT °C.	>155
FREEZING POINT °C.	-50

### DESCRIPTION

TORQUE P.S.F. IS A FLUID SPECIALLY FORMULATED WITH SYNTHETIC HYDROCARBONS FOR HYDRAULIC CIRCUITS DEVELOPED SPECIFICALLY FOR USE IN VEHICLES EQUIPPED WITH HYDRAULIC CIRCUITS, POWER STEERING, BRAKES, DAMPING AND HYDROPNEUMATIC SUSPENSIONS, USED BY AUDI, VW, SEAT, CITRÖEN, BMW, PEUGEOT, VOLVO, ETC. ITS USE IS INTENDED EXCLUSIVELY FOR VEHICLES REQUIRING THE SPECIFIED QUALITY LEVELS.

### MAIN ADVANTAGES

- EXCELLENT LUBRICATING AND ANTI-WEAR PROPERTIES.
- HIGH RESISTANCE TO OXIDATION AND AGEING.
- MINIMAL FOAMING AND ALMOST NO SLUDGE FORMATION.
- VERY HIGH VISCOSITY INDEX.
- COMPATIBILITY WITH SEALS AND SEALANTS.
- DO NOT MIX WITH CONVENTIONAL BRAKE FLUIDS.
- DO NOT MIX WITH MINERAL BASED L.H.M. FLUIDS.
- DO NOT USE FOR AUTOMATIC GEARBOXES, DO NOT MIX WITH A.T.F. TYPE LUBRICANT.
- THE USE OF THIS FLUID REQUIRES VERIFICATION OF MANUFACTURERS' SPECIFICATIONS, AND THAT IT IS USED IN ACCORDANCE WITH THE VEHICLE MANUFACTURER'S INSTRUCTIONS.

QUALITY LEVELS
M.B. 236.3
NISSAN PSFII
HYUNDAI - PSF-III
FORD M2C195-A
MITSUBISHI - PS FLUID
CHRYSLER MS1872 - 5931