

TORQUE

HYDRAULIC FLUID



CHF

DATASHEET

TECHNICAL PHYSICAL DATA	
COLOR	GREEN
VISCOSITY 100 °C.	6,2 cST
VISCOSITY 40 °C.	18,9 cST
VISCOSITY -40 °C.	1100
VISCOSITY INDEX	>310
FLASH POINT °C.	>155
FREEZING POINT °C.	-52

DESCRIPTION

TORQUE CHF IS A FLUID SPECIALLY FORMULATED WITH SYNTHETIC HYDRAULICS FOR HYDRAULIC CIRCUITS SPECIFICALLY DEVELOPED FOR USE IN VEHICLES EQUIPPED WITH A CENTRALIZED HYDRAULIC CIRCUIT, POWER STEERING, BRAKES, DAMPING AND HYDROPNEUMATIC SUSPENSIONS, USED BY AUDI, VW, SEAT, CITRÖEN, BMW, PEUGEOT AND VOLVO. SUITABLE FOR VEHICLES EQUIPPED WITH ABS/ASR/ASC SYSTEM. ITS USE IS INTENDED EXCLUSIVELY FOR VEHICLES THAT REQUEST THE SPECIFIED QUALITY LEVELS.

• MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- MINIMAL FOAM FORMATION, AND ALMOST NO SLUDGE.
- COMPATIBILITY WITH GASKETS AND SEALANTS.
- DO NOT MIX WITH CONVENTIONAL BRAKE FLUIDS.
- DO NOT MIX WITH MINERAL-BASED FLUIDS L.H.M.
- DO NOT USE FOR AUTOMATIC GEARBOXES, NOR MIX WITH A.T.F TYPE LUBRICANT.
- THE USE OF THIS FLUID REQUIRES VERIFICATION OF THE MANUFACTURERS' SPECIFICATIONS, AND THAT IT BE USED FOLLOWING THE INSTRUCTIONS OF THE VEHICLE MANUFACTURER.

QUALITY LEVELS	
VW TL 52146 (G-2000), (G-2012) Y (G-4000)	
A 26.090.88	MB.345.0
DIN 51 524 T2	ISO 7308
VOLVO STD 1273.36	PENTOSIN CHF 11S
CITRÖEN B 71 27 10	FORD M2C195-A Y M2C204-A
HYUNDAI/KIA-PSF 3 Y 4	TOYOTA PSF
NISSAN PSFII	MITSUBISHI - PS FLUID Y SPIII

Nerol, the Nerol logo and associated trademarks are registered trademarks of Nerol Lubricants S.L. Used under license.

This data sheet and the information contained herein are believed to be correct at the time of printing. No representation or warranty, direct or implied, is made as to the accuracy or completeness of the data and information contained in this publication. The data provided are based on standard tests carried out under laboratory conditions and are intended for guidance only. Users should ensure that they are using the latest version of this data sheet. It is the responsibility of the user to evaluate and use the products safely, to assess their suitability for the intended application and to comply with all applicable laws and regulations. Safety data sheets are available for all products and should be consulted for proper information on storage, safe handling and transfer or sale of the product. Neither Nerol nor any of its affiliates shall be liable for damages resulting from improper use of the material, failure to follow recommendations, or hazards inherent in the nature of the material. All products, services and information supplied are subject to our terms and conditions of sale. Please consult your local representative for further information.