

NE147900 - NEROL AUTO VALVULINA 85W140 GL5

1.1	Product identifier:	NE147900 - NEROL AUTO VALVULINA 85W140 GL5				
	Other means of identification					
	UFI:	5K50-T05H-400Y-T5WP				
2	Relevant identified uses of t	he substance or mixture and uses advised against:				
	Relevant uses: Mineral-based motor oil					
	Uses advised against: All uses no	ot specified in this section or in section 7.3				
3	-					
4	Nerol Lubricants, S.L. Ctra. de Mazarrón Km. 3 - Cartag 30393 Murcia - Murcia - España Phone: +34911271060 info@lubricantsnerol.com www.lubricantsnerol.com Emergency telephone numbe	gena er: (+353) 01 809 2166 (8 am. 10 pm) EUROPE : +44 (0) 1235 239 670				
SEC	TION 2: HAZARDS IDENTIFIC	ATION				
2.1	Classification of the substan	ce or mixture:				
	CLP Regulation (EC) No 1272	2/2008:				
	Classification of this product has	been carried out in accordance with CLP Regulation (EC) No 1272/2008.				
	Aquatic Chronic 3: Hazardous to	the aquatic environment, long-term hazard, Category 3, H412				
2.2	Label elements:					
	CLP Regulation (EC) No 1272	2/2008:				
	Hazard statements:					
	Aquatic Chronic 3: H412 - Harm	ful to aquatic life with long lasting effects.				
	Precautionary statements:					
	Precautionary statements:					
	P101: If medical advice is neede P102: Keep out of reach of child P273: Avoid release to the envir					
	P101: If medical advice is neede P102: Keep out of reach of child P273: Avoid release to the envir	Iren. onment. ainer according to the separated collection system used in your municipality.				
	P101: If medical advice is neede P102: Keep out of reach of child P273: Avoid release to the envir P501: Dispose of contents/conta Supplementary information : EUH208: Contains Reaction proc	Iren. onment. ainer according to the separated collection system used in your municipality.				

2.3 Other hazards:

Product does not meet PBT/vPvB criteria Endocrine-disrupting properties: The product does not meet the criteria.

Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mineral oil

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification				
CAS: EC:	Non-applicable 931-384-6		eaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus Self-classified kide, propylene oxide and amines, C12-14-alkyl (branched) ⁽¹⁾				
Index: REACH:	Non-applicable 01-2119493620-38- XXXX Acute Tox. 4: H302; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Sens. 1: H317 -				1 - <2,5 %		
CAS:	112-90-3	(Z)-octadec-9-enyla	nine ⁽¹⁾	ATP ATP05			
EC: Index: REACH:	204-015-5 612-283-00-3 Non-applicable	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Skin Corr. 1B: H314; STOT RE 2: H373; STOT SE 3: H335 - Danger		<1 %		
CAS:	95-63-6	1,2,4-trimethylbenze	ene ⁽²⁾	ATP CLP00			
EC: Index: REACH:	202-436-9 601-043-00-3 01-2119472135-42- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	() () ()	<1 %		

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

	Identification			M-factor
(Z)-octadec-9-enylar	nine		Acute	10
		Chronic	10	
	Identification	Spec	ific concentrat	ion limit
	bis(4-methylpentan-2-yl)dithiophosphoric acid with ropylene oxide and amines, C12-14-alkyl (branched)	% (w/w) >=50: Eye Irrit. 2 % (w/w) >=9,39: Skin Sens		

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Version: 1

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:



SECTION 5: FIREFIGHTING MEASURES (continued)

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 7: HANDLING AND STORAGE (continued)

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

 Minimum Temp.:
 5 °C

 Maximum Temp.:
 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
1,2,4-trimethylbenzene	WEL (8h)	25 ppm	125 mg/m ³
CAS: 95-63-6 EC: 202-436-9	WEL (15 min)		

Oils: WEL (15 min)= 10 mg/m3

DNEL (Workers):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
EC: 931-384-6	Inhalation	Non-applicable	Non-applicable	4,28 mg/m ³	Non-applicable
1,2,4-trimethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 95-63-6	Dermal	Non-applicable	Non-applicable	16171 mg/kg	Non-applicable
EC: 202-436-9	Inhalation	100 mg/m ³	100 mg/m ³	100 mg/m ³	100 mg/m ³

DNEL (General population):

		Short e	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Oral	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	6,25 mg/kg	Non-applicable
EC: 931-384-6	Inhalation	Non-applicable	Non-applicable	1,09 mg/m ³	Non-applicable
1,2,4-trimethylbenzene	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
CAS: 95-63-6	Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
EC: 202-436-9	Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³

PNEC:

Identification				
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	STP	24,33 mg/L	Fresh water	0,0024 mg/L
CAS: Non-applicable	Soil	0,00117 mg/kg	Marine water	0,00024 mg/L
EC: 931-384-6	Intermittent	0,15 mg/L	Sediment (Fresh water)	0,0129 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	0,00129 mg/kg



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued

Identification				
1,2,4-trimethylbenzene	STP	2,41 mg/L	Fresh water	0,12 mg/L
CAS: 95-63-6	Soil	2,34 mg/kg	Marine water	0,12 mg/L
EC: 202-436-9	Intermittent	0,12 mg/L	Sediment (Fresh water)	13,56 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	13,56 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):

0,01 % weight



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECT	TION 8: EXPOSURE CONTROLS/P	ERSONAL PROTECTION (continued)	
	V.O.C. density at 20 °C:	0,13 kg/m³ (0,13 g/L)	
	Average carbon number:	9	
	Average molecular weight:	120,2 g/mol	
SECT	TION 9: PHYSICAL AND CHEMICA		
9.1	Information on basic physical an		
9.1	For complete information see the pro		
	Appearance:		
	Physical state at 20 °C:	Liquid	
	Appearance:	Oily	
	Colour:	Amber	
	Odour:	Lubricant	
	Odour threshold:		
		Non-applicable *	
	Volatility:	-171 - 641 °C	
	Boiling point at atmospheric pressure		
	Vapour pressure at 20 °C:	6 Pa	
	Vapour pressure at 50 °C:	2000 Pa (2 kPa)	
	Evaporation rate at 20 °C:	Non-applicable *	
	Product description:		
	Density at 20 °C:	910 kg/m ³	
	Relative density at 20 °C:	0,91	
	Dynamic viscosity at 20 °C:	1 cP	
	Kinematic viscosity at 20 °C:	1,19 mm²/s	
	Kinematic viscosity at 40 °C:	330 mm²/s	
	Kinematic viscosity at 100 °C:	27 mm²/s	
	Concentration:	Non-applicable *	
	pH:	Non-applicable *	
	Vapour density at 20 °C:	Non-applicable *	
	Partition coefficient n-octanol/water 2	0 °C: Non-applicable *	
	Solubility in water at 20 °C:	Non-applicable *	
	Solubility properties:	Insoluble in water, soluble in organic solvents	
	Decomposition temperature:	Non-applicable *	
	Melting point/freezing point:	Non-applicable *	
	Flammability:		
	Flash Point:	200 °C	
	Flammability (solid, gas):	Non-applicable *	
	Autoignition temperature:	260 °C	
	Lower flammability limit:	Non-applicable *	
	Upper flammability limit:	Non-applicable *	
	Particle characteristics:		
	Median equivalent diameter:	Non-applicable	
9.2	Other information:		
	Information with regard to physi	cal hazard classes:	
	*Not relevant due to the nature of the produc	t, not providing information property of its hazards.	

- CONTINUED ON NEXT PAGE -

Version: 1



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIE	ES (continued)	
Explosive properties:	Non-applicable *	
Oxidising properties:	Non-applicable *	
Corrosive to metals:	Non-applicable *	
Heat of combustion:	Non-applicable *	
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *	
Other safety characteristics:		
Surface tension at 20 °C:	Non-applicable *	
Refraction index:	Non-applicable *	
*Not relevant due to the nature of the product, not providing information property of its hazards.		

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION


11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):





SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Distillates (petroleum), solvent-dewaxed heavy paraffinic, < 3% DMSO (3); Distillates (petroleum), hydrotreated light paraffinic, < 3% DMSO (> 20.5 cSt 40°C) (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
(Z)-octadec-9-enylamine	LD50 oral	888 mg/kg	Rat
CAS: 112-90-3	LD50 dermal	Non-applicable	
EC: 204-015-5	LC50 inhalation	Non-applicable	
1,2,4-trimethylbenzene	LD50 oral	3400 mg/kg	Rat
CAS: 95-63-6	LD50 dermal	3160 mg/kg	Rabbit
EC: 202-436-9	LC50 inhalation	11 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 12: ECOLOGICAL INFORMATION (continued) Identification Concentration Species Genus Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 LC50 >1 - 10 mg/L (96 h) Fish -alkyl (branched) EC50 >1 - 10 mg/L (48 h) CAS: Non-applicable Crustacean EC: 931-384-6 EC50 >1 - 10 mg/L (72 h) Algae C50 >0,1 - 1 mg/L (96 h) Fish (Z)-octadec-9-enylamine CAS: 112-90-3 >0,1 - 1 mg/L (48 h) Crustacean EC50 EC: 204-015-5 EC50 >0,1 - 1 mg/L (72 h) Algae 1,2,4-trimethylbenzene LC50 7,72 mg/L (96 h) Pimephales promelas Fish CAS: 95-63-6 EC50 6,14 mg/L (48 h) Daphnia magna Crustacean EC: 202-436-9 EC50 Non-applicable

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
1,2,4-trimethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 95-63-6	COD	Non-applicable	Period	28 days
EC: 202-436-9	BOD5/COD	Non-applicable	% Biodegradable	18 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
1,2,4-trimethylbenzene	BCF	154
CAS: 95-63-6	Pow Log	3,78
EC: 202-436-9	Potential	High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
1,2,4-trimethylbenzene	Кос	537	Henry	624,16 Pa·m ³ /mol
CAS: 95-63-6	Conclusion	Low	Dry soil	Yes
EC: 202-436-9	Surface tension	2,919E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2. **Regulations related to waste management:**



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



SECTION 16: OTHER INFORMATION (continued)
Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation.
Classification procedure:
Aquatic Chronic 3: Calculation method
Advice related to training:
Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.
Principal bibliographical sources:
http://echa.europa.eu http://eur-lex.europa.eu
Abbreviations and acronyms:
ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Version: 1