

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: NE147900 - NEROL AUTO VALVULINA 85W140 GL5 Other means of identification: Non-applicable 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Mineral-based motor oil Uses advised against: All uses not specified in this section or in section 7.3 1.3 Details of the supplier of the safety data sheet: Nerol Lubricants, S.L. Ctra. de Mazarrón Km. 3 - Cartagena 30393 Murcia - Murcia - España

info@lubricantsnerol.com
www.lubricantsnerol.com **1.4 Emergency telephone number:** EUROPE : +44 (0) 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation:

Phone: +34911271060

Classification of this product has been carried out in accordance with GB CLP Regulation.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

GB CLP Regulation:

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P501: Dispose of the contents and/or its container using the separate collection system in your municipality.

Supplementary information:

EUH208: Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mineral oil

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	
CAS:	Non-applicable	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) Acute Tox. 4: H302; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	1 - <2,5 %
CAS:	112-90-3	(Z)-octadec-9-enylamine Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Skin Corr. 1B: H314; STOT RE 2: H373; STOT SE 3: H335 - Danger	<1 %

Safety data sheet According to UK REACH



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

Indication of any immediate medical attention and special treatment needed:

Non-applicable

4.3

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Technical measures for storage
 - Minimum Temp.:5 °CMaximum Temp.:30 °CMaximum time:6 Months
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

Oils: WEL (15 min)= 10 mg/m3

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

Version: 1



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	12.5 mg/kg	Non-applicable
EC: 931-384-6	Inhalation	Non-applicable	Non-applicable	4.28 mg/m ³	Non-applicable

DNEL (General population):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	Oral	Non-applicable	Non-applicable	0.25 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	6.25 mg/kg	Non-applicable
EC: 931-384-6	Inhalation	Non-applicable	Non-applicable	1.09 mg/m ³	Non-applicable

PNEC:

Identification				
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	STP	24.33 mg/L	Fresh water	0.0024 mg/L
CAS: Non-applicable	Soil	0.00117 mg/kg	Marine water	0.00024 mg/L
EC: 931-384-6	Intermittent	0.15 mg/L	Sediment (Fresh water)	0.0129 mg/kg
	Oral .	0.01 g/kg	Sediment (Marine water)	0.00129 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer 's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposur to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.



Pictogram	PPE		Remarks			
	Anti-slip work shoes	to the product for professional/in	erioration. For periods of prolonged expos ndustrial users CE III is recommended, in n EN ISO 20345:2012 y EN 13832-1:200			
F Additional emergency measur	res					
Emergency measure	Standards	Emergency measure	Standards			
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:201	L Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201			
Environmental exposure cont	trols:					
In accordance with the communi spillage of both the product and i The Volatile Organic Compou V.O.C. (Supply): V.O.C. density at 20 °C:	its container. For additional inf	ormation see subsection 7.1. Ind Vehicle Refinishing Pro-)			
TION 9: PHYSICAL AND CHEM	ICAL PROPERTIES					
Information on basic physical and chemical properties:						
For complete information see the product datasheet.						
Appearance:						
Physical state at 20 °C:	Liquid					
Appearance:	Oily					
Colour:	A	nber				
Odour:	Lubric	ant				
Odour threshold:	Non-a	pplicable *				
Volatility:						
Volatility: Boiling point at atmospheric pres	sure: -171 -	641 °C				
-	sure: -171 - 6 Pa	641 °C				
Boiling point at atmospheric pres	6 Pa	641 ºC Pa (2 kPa)				
Boiling point at atmospheric pres Vapour pressure at 20 °C:	6 Pa 2000					
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C:	6 Pa 2000	Pa (2 kPa)				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C:	6 Pa 2000	Pa (2 kPa) pplicable *				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description:	6 Pa 2000 Non-a	Pa (2 kPa) pplicable *				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C:	6 Pa 2000 Non-a 910 kg	Pa (2 kPa) pplicable *				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C:	6 Pa 2000 Non-a 910 k 0.91 1 cP	Pa (2 kPa) pplicable *				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	6 Pa 2000 Non-a 910 k 0.91 1 cP	Pa (2 kPa) pplicable * g/m ³ nm ² /s				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C:	6 Pa 2000 Non-a 910 kg 0.91 1 cP 1.19 r	Pa (2 kPa) pplicable * g/m ³ nm ² /s				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C:	6 Pa 2000 Non-a 910 kg 0.91 1 cP 1.19 r 330 m 27 mr	Pa (2 kPa) pplicable * g/m ³ nm ² /s				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Kinematic viscosity at 100 °C:	6 Pa 2000 Non-a 910 k 0.91 1 cP 1.19 r 330 m 27 mr Non-a	Pa (2 kPa) pplicable * g/m ³ nm ² /s n ² /s				
Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Kinematic viscosity at 100 °C: Concentration:	6 Pa 2000 Non-a 910 kg 0.91 1 cP 1.19 r 330 m 27 mr Non-a Non-a	Pa (2 kPa) pplicable * g/m ³ nm ² /s n ² /s pplicable *				
Boiling point at atmospheric pres Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Kinematic viscosity at 100 °C: Concentration: pH:	6 Pa 2000 Non-a 910 k 0.91 1 cP 1.19 r 330 m 27 mr Non-a Non-a Non-a	Pa (2 kPa) pplicable * g/m ³ nm ² /s n ² /s pplicable * pplicable *				
Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Kinematic viscosity at 100 °C: Concentration: pH: Vapour density at 20 °C:	6 Pa 2000 Non-a 910 k 0.91 1 cP 1.19 r 330 m 27 mr Non-a Non-a Non-a Non-a	Pa (2 kPa) pplicable * g/m ³ nm ² /s n ² /s pplicable * pplicable * pplicable *				

- CONTINUED ON NEXT PAGE -

Version: 1



SECT	TON 9: PHYSICAL AND CHEMICAL PROPERTIES	G (continued)
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	200 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	260 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard class	ses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Non-applicable *
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing inform	maion property of its indzards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

Version: 1

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Date of compilation: 23/06/2023

Safety data sheet According to UK REACH



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Distillates (petroleum), solvent-dewaxed heavy paraffinic, < 3% DMSO (3); Distillates (petroleum), hydrotreated light paraffinic, < 3% DMSO (> 20.5 cSt 40°C) (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
(Z)-octadec-9-enylamine	LD50 oral	888 mg/kg	Rat
CAS: 112-90-3	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	



SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 -alkyl (branched)	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
(Z)-octadec-9-enylamine	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 112-90-3	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment: Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils	Dangerous

Type of waste:

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:



SECTION 15: REGULATORY INFORMATION (continued)

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

--ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Corr. 1B: H314 - Causes severe skin burns and eve damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

Safety data sheet According to UK REACH



NE147900 - NEROL AUTO VALVULINA 85W140 GL5

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Version: 1