

PERFORMANCE VTX



5W-30 LTO

DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	5W30
VISCOSITY 100 °C. cST. (ASTM D445)	12
VISCOSITY INDEX, (ASTM D2270)	160
FLASH POINT °C. (ASTM D92)	225
FREEZING POINT °C. (ASTM D97)	-40
TBN. (ASTM D-2896)	>6

BUILDERS
GM-OPEL DEXOS 2
BMW Long Life-04
MB 229.52 / MB 229.51 (retro applicable MB 229.31)
VW 502.00/505.00/505.1

DESCRIPTION

PERFORMANCE VTX 5W30 LTO C3 / DEXOS 2, IS A HIGH QUALITY 100% SYNTHETIC LUBRICANT WITH GROUP III SYNTHETIC BASES AND SPECIFIC LATEST GENERATION ADDITIVES, INDICATED FOR USE IN MODERN GASOLINE AND DIESEL ENGINES SPECIFICALLY FORMULATED FOR GENERAL MOTORS, WHERE Its GM Dexos Specification is requested 2. The fluid has high lubrication properties to withstand the additional load of the Injector System Injector pump reducing frictions and increasing wear resistance at high temperatures, recommended for a long change interval according to recommendations according to recommendations FROM EACH MANUFACTURER. SUITABLE FOR ENGINES THAT ARE EQUIPPED WITH DIESEL PARTICULATE FILTER (DPF) SYSTEMS ACHIEVING A REDUCTION OF GAS EMISSIONS. AND SUITABLE FOR VEHICLES THAT INCORPORATE THE REGULATION OF GAS EMISSION IN GASOLINE/DIESEL ENGINES THAT REQUIRE LOW CONTENT OF SULFUR, SULFATED ASH AND PHOSPHORUS (MID SAPS, HALF SAPS).

MAIN ADVANTAGES

- HIGH LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- HIGH DETERGENT AND DISPERSANT POWER.
- GOOD PROTECTION AGAINST CORROSION.
- DECREASES OIL CONSUMPTION.
- USABLE IN WINTER AND SUMMER.
- REDUCES MAINTENANCE COST.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.
- IMPROVE COLD STARTING IN ALL SEASONS

QUALITY LEVELS	
ACEA	C3
API	SM - CF