

## 5W-30 PTB

### DATASHEET

TECHNICAL PHYSICAL DATA	
SAE GRADE	5W30
VISCOSITY 100 oC. cST.(ASTM D445)	12
VISCOSITY INDEX, (ASTM D2270)	150
FLASH POINT °C. (ASTM D92)	225
FREEZING POINT °C. (ASTM D97)	-38
TBN. (ASTM D-2896)	11

BUILDERS
M.B. 229.5
RENAULT RN 0700
VW 502.00 / 505.00
PSA - B71 2296
BMW LL-01
OPEL GM LL-A-025 / LL-B-025

### DESCRIPTION

TRACK 5W30 PTB IS A HIGH QUALITY SYNTHETIC LUBRICANT, SPECIALLY DESIGNED FOR USE IN LIGHT GASOLINE AND DIESEL ENGINES, (WITH AND WITHOUT CATALYST) INCLUDING HIGH POWER AND MULTI-VALVE TURBO CHARGED UNITS. IT HAS EXCELLENT COLD BEHAVIOR DUE TO ITS DESIGNED LOW VISCOSITY AND ITS SYNTHETIC NATURE, WHICH FACILITATES THE PUMPABILITY OF THE LUBRICANT, A REASON OF GREAT HELP IN COLD STARTING AND FILM FORMATION TO IMPORTANTLY REDUCE WEAR.

### MAIN ADVANTAGES

- EXCELLENT LUBRICANT AND ANTI-WEAR PROPERTIES.
- GREAT RESISTANCE TO OXIDATION AND AGING.
- HIGH DETERGENT AND DISPERSANT POWER.
- GOOD PROTECTION AGAINST CORROSION.
- DECREASES OIL CONSUMPTION.
- USABLE IN WINTER AND SUMMER.
- INCREASES THE OIL CHANGE PERIOD, THEREFORE, REDUCES THE MAINTENANCE COST.
- LUBRICANT TO BE USED WHERE THE MANUFACTURER REQUESTS THESE QUALITY LEVELS.
- IMPROVE COLD STARTING IN ALL SEASONS

QUALITY LEVELS	
ACEA	A3/B3 A3/B4
API	SM - CF